This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- (Original) A printing system comprising:
 an ink dispenser configured to deposit ink upon a print medium; and
 a condenser configured to condense vapor into a condensate;
 a receptacle configured to collect the condensate, wherein the
 receptacle is perforated to permit a portion of the condensate to evaporate.
- (Original) The system of Claim 1, wherein the condenser includes:

 a conduit having a conduit interior; and
 a coolant source connected to the conduit and configured to supply

 coolant into the conduit interior at a temperature so as to condense the vapor along the conduit.
- 3. (Original) The system of Claim 2, wherein the coolant source is configured to supply a liquid at a temperature so as to condense the vapor along the conduit.
- (Original) The system of Claim 2, wherein the coolant source is configured to supply a gas at a temperature so as to condense the vapor along the conduit.
- 5. (Original) The system of Claim 2, wherein the condenser includes a fin thermally coupled to the conduit.
- 6. (Original) The system of Claim 1, wherein the receptacle includes an inlet and means for automatically occluding the inlet when disconnected from a remainder of the printing system.

- 7. (Original) The system of Claim 2, wherein the coolant source includes: a pump configured to move fluid; and a cooling device configured to cool the fluid to the temperature.
- 8. (Original) The system of Claim 7, wherein the cooling device includes a compressor.
- 9. (Original) The system of Claim 1, wherein the condenser includes a thermoelectric module.
- 10. (Original) The system of Claim 1 including a blower configured to move the vapor along the condenser.
 - 11. (Original) The system of Claim 10 including:a duct proximate the condenser and having an exhaust opening; anda filter between the condenser and the exhaust opening.
- 12. (Original) The system of Claim 1, wherein the receptacle includes a condensate-absorbing material within the receptacle.
- 13. (Original) The system of Claim 12, wherein the condensate-absorbing material is removable from the receptacle.
- 14. (Original) The system of Claim 12, wherein the condensate-absorbing material comprises a foam.
- 15. (Original) The system of Claim 1, wherein the receptacle includes: an inlet through which the condensate flows into the receptacle; and a closing portion movable between an inlet open position and an inlet closing position.
- 16. (Original) The system of Claim 15, wherein the receptacle is removably coupled to a remainder of the system.

- 17. (Original) The system of Claim 1, wherein the receptacle includes a fill indicator configured to indicate a volume of the receptacle that is filled with condensate.
- (Original) The system of Claim 1, wherein the ink dispenser includes an inkjet printhead.
- 19. (Original) The system of Claim 1 including a media handling system configured to transport individual sheets of material relative to the ink dispenser.
- 20. (Original) The system of Claim 19, wherein the media handling system is configured to handle sheets of material having a minor dimension less than 9 inches.
- 21. (Original) The system of Claim 19, wherein the handling system is configured to stack the individual printed upon sheets.
- 22. (Original) The system of Claim 1 including a heater configured to heat the deposited ink, whereby vapor is produced.
 - 23. (Original) A condensate storage system comprising: a receptacle having an inlet; and a condensate-absorbing member within the receptacle.
- 24. (Original) The system of Claim 23, wherein the receptacle is perforate to permit a portion of the condensate to evaporate.
- 25. (Original) The system of Claim 23, wherein the receptacle and the condensate-absorbing member are configured to permit removal of the absorbing member from the receptacle.
- 26. (Original) The system of Claim 23, wherein the system is configured for use in a printing system having an outer housing and wherein the receptacle is configured to be removably received within the housing.

- 27. (Original) A printing system comprising:
 means for depositing ink upon a print medium;
 means for condensing vapor to form a condensate; and
 means for storing the condensate, wherein the means for storing
 includes an inlet and means for automatically occluding the inlet when disconnected
 from a remainder of the printing system.
- 28. (Original) The system of Claim 27 including means for storing includes means for evaporating a portion of the condensate while the condensate is being stored.
- 29. (Original) The system of Claim 27 including means for heating the deposited ink, whereby vapor is formed.
- 30. (Original) A method of printing ink upon a medium, the method comprising:

depositing ink upon the medium;
heating the deposited ink to create a vapor;
condensing the vapor into a condensate;
collecting the condensate in a first receptacle; and
absorbing at least a portion of the condensate into a first absorption
member within the first receptacle.

- 31. (Original) The method of Claim 30 including circulating a fluid through a thermally conductive conduit having a condensing surface to cool the condensing surface to a temperature to condense the vapor.
- 32. (Original) The method of Claim 30 including powering a thermoelectric module having a cool portion and a hot portion, wherein the cool portion is thermally coupled to a condensing surface along which the vapor is condensed.

- 33. (Currently Amended) The method of Claim 49 30 including evaporating a portion of the condensate within the first receptacle.
- 34. (Original) The method of Claim 30 including replacing the first absorption member with a second absorption member.
- 35 (Original) The method of Claim 30 including replacing the first receptacle with a second receptacle when at least a portion of the first receptacle is filled with condensate.
- 36. (Original) The method of Claim 30 including sending the first receptacle at least partially filled with the condensate to a collection entity for recycling or disposal of the condensate.
- 37. (Original) The method of Claim 30 including sensing an amount of condensate within the first receptacle.
- 38. (Original) The method of Claim 30 including directing the vapor across a condensing surface and through a filter.
- 39. (Original) The method of Claim 30, wherein the step of depositing ink includes ejecting ink from an inkjet printhead upon the medium.